



A.G.A. Group
 Merton Hall Ponds
 Merton, Thetford
 Norfolk IP25 6QH
 Telephone: +44 (0) 1953 886824
 Email: info@agagroup.co.uk
www.agagroup.co.uk

Product Specification Sheet

A.G.A. Wood Systems

Reliable and environmentally acceptable materials for use in sustainable bio-engineering systems

A.G.A. wood product can be modified to suit the client's own specification.

Typical applications

- Erosion control, bank restoration and spilling for living revetments. Slope and bank stabilisation. A.G.A only use FSC certified suppliers to support best management practices of the world's forest.

Product	Dimensions		Material	Dry Weight	Binding
	Diameter	Length			
Faggots	400mm (Variable)	2m (Variable),	Hazel, Chestnut	6 kg per m	Polypropylene multi-strand fibre twine.
	300mm (Variable)	2m (Variable)	Live Willow	12kg per m	3 ties per bundle
Spilling			Live willow withies and stakes		
Osiers	Specified size		Live Willow		
Weips	300mm	1 to 15 meters	Willow		Polypropylene twine
Supports Rails & Fencing	50mm x	1.2m – 1.8m – 2.2m	Treated softwood		
	75 – 80mm	1.2m – 1.8m – 2.2m			
	80 – 100mm	1.8m – 2.2m			
	80 – 100mm	1.8m – 2.2m	Machined & treated		
	75 – 80mm	1.8m – 2.2m	Clefted Chestnut		
	80 – 100mm	1.8m – 2.2m			
Posts	50mm x	1.2m – 1.8m – 2.2m	Treated softwood		
	75 – 80mm	1.2m – 1.8m – 2.2m			
	80 – 100mm	1.8m – 2.2m			
	80 – 100mm	1.8m – 2.2m	Machined & treated		
	75 – 80mm	1.8m – 2.2m	Clefted Chestnut		
	80 – 100mm	1.8m – 2.2m			

Typical A.G.A Wood products Hazel - Chestnut – Willow, softwoods and brushwood is harvested from plantations and as a renewable source, has no detrimental effect on the environment.

The A.G.A. Group provided this information for reference purposes only. This specification is not intended as a warranty or guarantee. The company assumes no liability in connection with the use of this information.

Please contact us for current specifications and changes arising from new developments.

